

Appl. No. 10/539,895
Reply to Office Action of August 8, 2008
Attorney Docket 18064

RECEIVED
CENTRAL FAX CENTER
DEC 08 2008

AMENDMENTS TO THE CLAIMS

This listing of claims will replace all prior versions, and listings, of claims:

1. (currently amended) In a road grader having a rear frame including left and right longitudinal beams, each having a rear end, and providing for the components or subassemblies of a rear counterweight, lights and a bumper, the improvement comprising

the bumper and the rear counterweight having a first and second configuration and are comprised of a first or a second [[a]] generally flat elongate rear end plate having opposing outer end regions and extending across the entire width of the grader;

in a first configuration the first rear end plate exhibits a small wall thickness in use and is connected to the grader in combination with a rear-mounted piece of equipment of a high weight and [[or]] in a second configuration the second rear end plate exhibits a greater wall thickness than the wall thickness of the first rear end plate and is connected to the grader in combination in-use with a rear-mounted piece of equipment of a [[low]] lower weight than the piece of equipment of the first configuration or without any rear-mounted equipment, ~~such that an axle load distribution of the grader is generally maintained;~~

the rear end plate viewed in the direction of travel of the grader constitutes the rearmost part of the rear frame; and

~~backup/brake and flasher lights are built into openings in the rear end plate~~

Appl. No. 10/539,895
Reply to Office Action of August 8, 2008
Attorney Docket 18064

~~positioned in the outer end regions.~~

2. (original) The improvement of claim 1, wherein:
the rear end plate is formed as one piece.
3. (original) The improvement of claim 2, wherein:
the rear ends of the left longitudinal beam and the right longitudinal beam are joined
to a rear transverse beam.
4. (original) The improvement of claim 3, wherein:
the rear end plate is removably attached to the rear transverse beam.
5. (original) The improvement of claim 1, wherein:
the rear ends of the left longitudinal beam and the right longitudinal beam are joined
to a rear transverse beam.
6. (canceled) The improvement of claim 2, wherein:
the rear ends of the left longitudinal beam and the right longitudinal beam are
joined to a rear transverse beam.
7. (canceled) The improvement of claim 3, wherein:
the rear end plate is removably attached to the rear transverse beam.
8. (currently amended) A road grader comprising:

Appl. No. 10/539,895
Reply to Office Action of August 8, 2008
Attorney Docket 18064

a wheel-supported main frame having a front end and an opposing rear end as determined by the normal direction of travel, the main frame comprised of joined front and rear frames,

an engine and a driver's cab supported on said main frame;

a vertically adjustable ground-engaging blade supported by said main frame;

the rear frame having left and right longitudinal beams generally parallel and in the general same horizontal plane, each with a rear end,

a generally flat elongate rear end plate jointed to the rear end of each of the right and left longitudinal beams; the rear end plate constituting the rearmost part of the rear frame and extending generally the width of the road grader;

the rear end plate having openings therethrough along a bottom edge of the plate to allow rear-mounted equipment to pass from a position below the plate through a lower portion of the rear end plate.

9. (original) The road grader of claim 8, wherein:

the rear end plate is formed as one piece.

10. (original) The road grader of claim 9, wherein:

the rear end plate is removably attached to the rear transverse beam.

11. (original) The road grader of claim 8, wherein:

the rear end plate has opposing outer end portions and openings through the outer end portions and backup/brake and flasher lights are fitted therein.

Appl. No. 10/539,895
Reply to Office Action of August 8, 2008
Attorney Docket 18064

12. (original) The road grader of claim 11, wherein:

the rear end plate is made of heavy gauge steel.

13. (currently amended) The road grader of claim 8, wherein:

the grader has a first and second counterweight configuration, in the first configuration the rear end plate has a first weight and exhibits a small wall thickness and attached to the grader in combination in use with a first rear-mounted piece of equipment of a high weight [[or]] and the second configuration wherein the rear end plate is replaced by an auxiliary end plate that exhibits a greater wall thickness than the rear end plate and attached to the grader in combination in use with a second rear-mounted piece of equipment of a [[low]] lower weight than the first rear-mounted equipment or without any rear-mounted equipment to achieve an improved axle load distribution.

14. (new) A method for maintaining an improved axle load distribution between front wheels and an axle of a road grader having a rear frame including left and right longitudinal beams, each having a rear end, a bumper and counterweight of the grader comprising a generally flat elongate end plate extending across the width of the grader and connected to the rear end of the longitudinal beams, the steps comprising:

removing a first rear end plate having a first weight and first wall thickness from an end of the grader;

attaching a rear mounted piece of equipment to the end of the grader; and

attaching a second end plate having a second weight less than the first weight

Appl. No. 10/539,895
Reply to Office Action of August 8, 2008
Attorney Docket 18064

and a second thickness less than the first wall thickness to the end of the grader.